

Hi Talk


HD-100

LICENSE-FREE

Two Way Radio




With a compact, ergonomics design.
50 CTCSS 210 DCS avoid hearing on the same channel extra call.
HD-100 features a time-out timer (TOT) to avoid inadvertent continuous operation.





HD 100

Frequency: 433.050 - 433.500 MHz
Power: 0.5W
Voltage: DC 3.7V

Hi talk technology

MADE IN CHINA



Hi Talk HD-100



License-free Two Way Radio

Feature

- VOX function
- Scan function
- CTCSS and DCS
- DCS encrypt
- Busy Chammel lockout (BCL)
- Adjust squelch level
- Monitor
- Time-out timer (TOT)
- Battery save
- Scrambler
- Voice companding function

Transmitter

Output power	0.5W
Modulation	F3E
Current	≤1.2A
Modulation distortion	≤5%(300-3000Hz)
Maximum frequency deviation	≤2.5KHz
Remnant modulation	≤-35dB

Receiver

RF sensitivity	≤0.3μV
Silent sensitivity	≤0.25μV
Audio frequency power	≥250mW
Related audio distortion	≤5%
Modulation receiver bandwidth	±7KHz
Spurious rejection	≥55dB
Selectivity	≥65dB
Inter-modulation	≥60dB

Technical Specification

Frequency range	433.05 - 433.50MHz	Frequency stability	±2.5ppm
Channel	35	Operating temperature range	-20 C~+55 C
Channel spacing	12.5 KHz	Dimensions	105 x 59 x 34mm
Operation voltage	3.7V	Weight(with antenna and battery)	185g
Battery	1250mAh(Li-ion)		

Standard Accessories



Charger




Belt Clip



Hand Strap



Battery



User's Manual